



POINT OBSTRUCTION LIGHTS POL LED v5 POINTSPEC® SERIES

Compliances: ETL Listed to UL 1598A Marine Vessels at -40 deg C to +55 deg C
 ETL Listed to CSA C22.2 No. 137-M1981 & No. 250.0-08 Canada
 ETL Listed to UL 1598 at -40 deg C to +55 deg C
 ETL Verified FAA L-810 to FAA AC 150/5345-43H at -55 deg C to +55 deg C
 Registered ISO 9001: 2015
 Compliance to ICAO Annex 14 Low Intensity Types A (10 cd) & B (32 cd)
 Compliance to CL810 Transport Canada CAR 621, Table 13-2
 Compliance to CAP 437 & UK CAP 168 Table 6A.1 Low Intensity (Group A)
 IMO 2009 MODU Code (2010) paragraphs 13.5.24 & 13.5.25
 American Bureau of Shipping (ABS) Type Approved Product

The POL LED red low intensity obstruction lights are for use on aviation obstructions.

- The casting is copper-free (< 0.25%) aluminum.
- The lens is glass.
- The hardware is 316 (A4) stainless steel.
- The LED's are rated for 100,000 hours.
- Only 1.5 watts per head for 120V.
- IP66 tested and listed.
- Standard with the exclusive yellow Point Lighting Marine Treatment finish that is bonded to the metal and far exceeds the corrosion resistance of the standard FAA approved finish.
- Six (6) years limited warranty subject to Point Lighting "Terms & Conditions of Sale".

Point Type	Power*	Specification	Color	Mounting	Style	Options^
POL-21005	1: 120v 2: 220v 3: 12v DC 4: 24v DC 5: 48v DC 6: 277v	B: ICAO Types A & B B: Trans. Canada B: UK CAP 168 Group A	R: Red	34B: ¾-inch, Bottom 10B: 1-inch, Bottom 34F: ¾-in, Feed-thru M20B: Metric, Bottom SF: Slipfitter 2.375-in (60 mm)	S: Single D: Double See page 3	NC: NVG Compatible CF: Cable Fitting P: Photoelectric Controller ^ See page 4

POL-21005-1B-R-34B-D
DOUBLE OBSTRUCTION LIGHT



POL-21005-1B-R-34B-S
SINGLE OBSTRUCTION LIGHT



* AC voltages are nominal. See page 4 for operating range; suitable for 50 or 60 Hz.
 For mounting options and plan details, see file 0MOUNTINGS
 All details are available as AutoCAD files for project plans
 FAA approved "lamp" number 631.



POL-21005-1B-R-34F-S3
SINGLE OBSTRUCTION LIGHT
WITH SIDE-WALL MOUNT JUNCTION BOX



POL-21005-1B-R-SF-S
SINGLE OBSTRUCTION LIGHT
WITH 60MM SLIPFITTER
FITS 2-3/8-INCH TENON



POL-21007-5B-R-SOL
PORTABLE SOLAR POWERED LIGHT
SEE FILE OL188POLV7



POL-21005-1F-R-34B-EX-MT
SINGLE OBSTRUCTION LIGHT
CLASS I, DIVISION 2
SEE FILE OL194POLEX



POL-21005-1B-R-34B-D-P
DOUBLE OBSTRUCTION LIGHT
WITH PREWIRED
FAA PHOTOELECTRIC CONTROL



POL-21005-1B-R-34B-S3-MT
SINGLE OBSTRUCTION LIGHT
WITH GREEN MARINE TREATMENT
& JUNCTION BOX



POL-21005-1B-R-34B-S3-P
SINGLE OBSTRUCTION LIGHT
WITH JUNCTION BOX & PREWIRED
FAA PHOTOELECTRIC CONTROL



FAA PHOTOELECTRIC CONTROLLER
PPC-40700-1-34T
SEE FILE OL410PPC



STYLE SELECTION CHART POINT OBSTRUCTION LIGHTS POL v5

Style	Transfer	Alarm Non-Isolated	Alarm Isolated	Pilot Light	Flashing	Description
-S						Standard Single
-S1					■	Single flashing (no junction box & no sync)
-S15					■	Single flashing, w/alarm line & J-box (Note 1 & no sync)
-S15K					■	As above only for use w/POC to flash all lights in sync
-S1.3					■	Single with junction box: flashing (Note 1)
-S2		■				Single: non-isolated alarm (Note 1)
-S2.1		■				DC only; same as Style –S2 for use with POC
-S3						Single: integral junction box & cover (Note 1)
-S4			■			Single: isolated failure alarm (Note 1)
-S5.3					□	Dual Mode Single: flashing, but may be set in the field to be steady-burning (Note 1)

-D						Double: both heads operating
-DT	■					Double: operating head & standby with transfer
-D1	■			■		Double: transfer & pilot light
-D2	■	■				Double: transfer & non-isolated alarm (Note 2)
-D2.2		■				Double: both heads operating & non-isolated alarm
-D3	■	■		■		Double: transfer, non-isolated alarm & pilot light
-D4	■		■			Double: transfer & isolated alarm (Note 2)
-D4.2			■			Double: both heads operating & isolated alarm
-D5	■		■	■		Same as Style –D4 with pilot light (Note 2)
-D6	■		■			Same as Style –D4 prewired with six (6) wires
-D7					■	Double: both heads flashing
-D8	■				■	Double: primary head flashes and transfer to standby head which flashes; no alarm
-D10	■	■			■	Same as Style –D8 with alarm line
-D10K	■	■			■	As above only for use w/POC to flash all lights in sync
-D13	■		■			Double: transfer, primary head alarm, standby head alarm & power failure alarm; tagged wires
-D14			■		■	Double: both heads flashing with isolated alarm
-D15		■			■	Double: both heads flashing; non-isolated alarm
-D15K		■			■	As above only for use w/POC to flash all lights in sync. Use for FAA A1 towers. No data cable. (Note 1)
-D16	■			■	■	Double: primary head flashes and transfer to standby head flashes; pilot light on transfer
-D18	■	■				Double: transfer, primary head alarm, standby head alarm; non-isolated alarms
-D19	■		■		■	Double: primary head flashes and transfer to standby head flashes; with isolated alarm line

Note 1: This single has a J-box & cover below the LED head assembly; box is required for any single with option –P.

Note 2: Alarm activates on transfer



SOLAR POWERED POL-21005 OBSTRUCTION LIGHTS

Choose one of the catalog numbers below to receive the mounting arrangement displayed in the graphic.

The POL-21005 is the proper selection for ICAO low intensity Types A & B and for Transport Canada CL810 certified by Intertek Testing Service.

The light will operate at night automatically year round anywhere the solar irradiance is greater than 1.0 kWh/m²/day.

Important - All POL-SOL systems by definition include:

- POL-21005 fixture
- Option -BKTU wall-post bracket** for the POL
- Option -CF cable fitting
- 3-meters SOW cable loop to the solar controller
- Solar array & solar controller with battery
- Floor-roof brackets* for the solar array

* Addition of option -PM changes to post brackets for the array & includes BKTU setup.

** See below for the POL bracket details.



POL-21005-3B-R-34B-S3-SOL



POL-21005-3B-R-34B-S3-SOL-PM

POL-21005 SINGLE WITH OPTION -BKTU
MAY BE WALL-MOUNTED OR POST-MOUNTED. THE POST MAY BE CONDUIT
OR PIPE TO A MAXIMUM OUTSIDE DIAMETER OF 3-INCHES (76MM).
THIS BRACKET IS INCLUDED IN ALL SOLAR POWER VERSIONS (-SOL)



TECHNICAL NOTES & OPTIONS

Alarm options must be selected at time of initial order. Alarms cannot be added in the field or retrofitted. POL LED lights cannot be monitored by 3rd party systems or controllers without selecting an alarm version of the POL LED. The POL optical subassembly is factory sealed to prevent moisture penetration and it is not serviceable.

Option –MT: Marine Treatment - Green Note: Yellow MT is standard
The fixture shall be treated for marine conditions by cleaning per US Department of Defense TT-C-490 method III, pretreated with chrome-free aluminum conversion coating per US MIL-C-5541 type II, epoxy powder base coat primer and glossy polyester powder coat finish in color RAL 6003 (FED-STD-595 color #14097) dark green. Powder coating per US Department of Defense MIL-PRF-24712A type VI and oven cured.

Option –NC: NVG Compatible
Adds infrared LED at 855 nm to allow visibility to pilots with or without night vision goggles.
Infrared Radiant Power F-array: 137 mW/sr B-array: 205 mW/sr

Option –P: Photoelectric Control
Adds a prewired FAA verified PEC to any single with a junction box or any double.

Option –FF: Floor Flange Mounting
Simple square flat mounting plate.

Option –CF: Cable Fitting
Cable compression fitting for outside diameter: 0.5 to 0.625-inch (12.7 to 15.9-mm). We suggest using with option -BKTU bracket kit.

Option –BKTU: Mounting Bracket Kit see Details in the file OPOINT BRACKETS
All-purpose aluminum bracket kit for single or double POL for wall-mount or with U-bolts to clamp to the structure.
Note: Solar power mounting option -PM includes the BKTU setup by definition.

Option –OS: Override Switch
For use with photoelectric controller option –P. Cover mounted 3-position switch ON-OFF-AUTO. Requires a double or single with junction box. For remote override switch, add item PL40110-3.

Option –SOL: Solar Powered
Solar power supply including array, controller & battery.

POWER CONSUMPTION PER POL LED LIGHT HEAD

Code	Type	Voltage	Frequency	Watts*	mA	VA*
-1B	ICAO B & TRAN CAN	120 AC	50/60 Hz	6.9	63	7.6
-2B	ICAO B & TRAN CAN	220 AC	50/60 Hz	6.9	34	7.4
-3B	ICAO B & TRAN CAN	12 DC	---	4.3	470	4.3
-4B	ICAO B & TRAN CAN	24 DC	---	4.3	230	4.3
-5B	ICAO B & TRAN CAN	48 DC	---	5.0	104	5.0
-6B	ICAO B & TRAN CAN	277 AC	50/60 Hz	6.9	28	7.9

Note: For option –NC, add 1.0 watts (1.1 VA)

*Power consumption for AC units includes the effect of the unit’s power factor which accounts for the difference between watts and volt-amperes. Measurements were made at the nominal AC voltages. The operating range for 120v units: 93 - 144v; for 220v units: 176 - 250v; for 277v units: 263 -291v



POL LED SPECIFICATIONS

SPECIFICATIONS COMMON TO ALL POL LED VERSIONS

The red LED lighted (specify: voltage) aviation obstruction light shall be tested and certified ICAO low intensity Type B. The obstruction light shall operate properly at 50 or 60 Hz at an input voltage supply of 120V +/-20% (93V to 144V) or, for 220V units, 176V to 250V or, for 277V units, +/-5% (263V to 291V). Within the preceding ranges, the output to the LED board shall be a controlled, stabilized constant current. The obstruction light shall not exceed 1.5 watts per head for FAA L-810 at 120V.

The AC obstruction lights shall be listed *Suitable for Use in Wet Locations* to UL1598A Marine Vessels, UL1598 2nd Edition Luminaries; CSA C22.2 No. 250.0-04, 2nd Edition; UL50 11th Edition Standard for Enclosures for Electrical Equipment and CSA C22.2 No. 94-M91 Special Purpose Enclosures. Sealed to IP66 ingress protection.

Special Technical Note*: DC light fixtures shall be reverse polarity protected.

* Competitors' units will fail if installed with reverse polarity.

The unit shall have passed the FAA certification tests: the constant high temperature test to +130 deg F (+55 deg C) and the constant low temperature test to -67 deg F (-55 deg C) conducted in accordance with US MILSTD-810F, Method 501.4, Procedure II; the wind-blown rain test conducted in accordance with US MIL-STD-810F, Method 506.3, Procedure I; and the humidity test shall be in accordance with US MIL-STD-810E, Method 507.3, Procedure I. The complete test regime shall exceed the requirements of NEMA 4X and IP 66. The light head shall be marine treated aviation yellow for high corrosion resistance certified by the manufacturer to comply with the US Military Standard Salt Fog Test conducted per MIL-STD-810F, Method 509.4, Procedure I, paragraph 4.5.2.

The clear lens shall be strong soda lime glass with the wave-length matched to the LEDs to permit the fullest light transmission. The lens shall be smooth and rounded to reduce the adhesion of dirt, ice and snow.

The red emitting LEDs shall meet the chromaticity requirements of US MIL-C-25050. The high output LEDs shall not exceed five (5) in number and shall be the latest technology providing uniform light output over the range required by the governing standard. The LED average life shall exceed 100,000 hours.

The LEDs shall be soldered in a factory set position to insure consistent light output. Wire mounted raised LEDs that can be bent out of position shall be unacceptable and cause for rejection. The LED board shall be treated with a protective dielectric conformal coating for protection from moisture and corrosion.

The power supply board shall include short circuit and open circuit protection and the unit shall be protected from line surges by metal oxide varistors (MOVs). All v5 units shall have the power supply and flasher board (if any) potted in the fixture (head subassembly) casting. There shall be a clear design element for the dissipation of LED heat to insure the LEDs do not fail prematurely.

The double LED light unit shall have an integral cast aluminum junction box with a minimum of 100 cubic inches of enclosed wiring space accessible from the front of the light unit. The wiring access cover shall be gasketed to be watertight, shall have captive screws and shall be secured to the unit with a tether. The cover tether and all hardware shall be stainless steel.

The red LED aviation obstruction light shall be POINTSPEC Series POL-21005 manufactured by Point Lighting Corporation.

Important Note: Alarm options must be selected at time of initial order. Alarms cannot be added in the field or retrofitted. POL LED lights cannot be monitored by 3rd party systems or controllers without selecting an alarm version of the POL LED.

WEIGHT, DIMENSIONS & SHIPPING DATA

inches (mm)						Multi-Pack Carton		
	Weight	Height	Width	Depth	Qty	Weight	Dim (inches)	
POINTSPEC Single:	3.5 lbs 1.6 kg	8.6 (217)	6.0 (152)	5.0 (127)	12	47 lbs 21.3 kg	22 x 15 x 17	
POINTSPEC Double:	11.8 lbs 5.4 kg	13.3 (337)	14.9 (378)	5.0 (127)	2	27 lbs 12.3 kg	19 x 19 x 19	
Wind Loading:	Effective Projected Area (EPA) for POINTSPEC Lights							
	Double: 0.69 sq ft	Single (no box): 0.19 sq ft	Single (with box): 0.37 sq ft					

POINT LIGHTING CORPORATION

Mail: P.O. Box 686, Simsbury, CT 06070
Tel 01 860.243.0600
email: Info@PointLighting.com

Plant: 61-65 W. Dudley Town Rd, Bloomfield, CT
USA
Fax 01 860.243.0665
website: www.PointLighting.com